

# RB951Ui-2HnD

The RB951Ui-2HnD is a wireless SOHO AP with a new generation Atheros CPU and more processing power. It has five Ethernet ports, one USB 2.0 port and a high power 2.4GHz 802.11b/g/n wireless AP with antennas built in.

It has a 600MHz CPU, 128MB of RAM and PoE output function for port #5 - it can power other PoE capable devices with the same voltage as applied to the unit. Maximum load on the port is 500mA.

Package contains RouterBOARD 951Ui-2HnD in a plastic case and power adapter. Specific frequency range may be limited by country regulations.



|                   |  |
|-------------------|--|
| Features          | RB951Ui-2HnD (USB, power injector, USB, 2GHz, 802.11n, dual chain) |
| CPU               | Atheros AR9344 600MHz CPU  |
| Memory            | 128MB DDR2 onboard memory  |
| Ethernet          | Five independent 10/100 Ethernet ports                             |
| LEDs              | Power, NAND activity, 5 Ethernet LEDs, wireless activity LED       |
| Power in          | PoE: 8-30V DC on Ether1 (Non 802.3af). Jack: 8-30V DC              |
| Power out         | PoE passive on port 5, same voltage as input.                      |
| Dimensions        | 113x138x29mm   |
| Weight            | Without packaging and PSU: 232g, full weight in package: 420g      |
| Power consumption | Up to 7W   |
| Operating Temp    | -20C .. +50C   |
| Operating System  | MikroTik RouterOS, Level4 license                                  |
| Package contains  | RouterBOARD in a plastic case, 24V 0.8A power adapter              |

|                |   |
|----------------|---|
| Antennas       | 2x2 MIMO PIF antennas, max gain 2.5dBi  |
| RX sensitivity | 802.11g: -96dBm @ 6Mbit/s to -80dBm @ 54Mbit/s<br>802.11n: -96dBm @ MCS0 to -78dBm @ MCS7 |
| TX power       | 802.11g: 30dBm @ 6Mbps to 25dBm @ 54 Mbps<br>802.11n: 30dBm @ MCS0 to 23dBm @ MCS7        |
| Modulations    | OFDM: BPSK, QPSK, 16 QAM, 64QAM; DSSS: DBPSK, DQPSK, CCK                                  |